

Drain pipe/skimmer and suction line specifications

	English	Metric	English	Metric	English	Metric	English	Metric
Internal diameter	3.0 in	7.6 cm	4.0 in	10.2 cm	6.0 in	15.2 cm	8.0 in	20.32 cm
Outer diameter	3.7 in	9.4 cm	4.7 in	11.9 cm	6.9 in	17.4 cm	9.1 in	22.90 cm
Linear weight empty	4.2 lbs/ft	6.3 kg/m	5.4 lbs/ft	8.0 kg/m	10.0 lbs/ft	15.0 kg/m	15.5 lbs/ft	23.1 kg/m
Minimum bending radius (storage)	2.0 ft	0.6 m	2.6 ft	0.8 m	3.7 ft	1.1 m	4.9 ft	1.5 m
Working pressure	30 psi	2.1 b	30 psi	2.1 b	30 psi	2.1 b	30 psi	2.1 b
Test pressure	60 psi	4.2 b	60 psi	4.2 b	60 psi	4.2 b	60 psi	4.2 b
Minimum Hydrostatic collapse pressure	190 psi	13 bars	145 psi	10 bars	115 psi	8 bars	87 psi	6 bars
Working temperature	Up to 100° C or 212° F							

NOTE : The design and characteristics of the pipe structure may be modified at any time by COFLEXIP.